

96-01-00

H

[56129050-3]

05/31/00

THE ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231
BOX PATENT APPLICATION

Transmitted herewith for filing is the patent application of Inventor(s): **Bruce Hodge**

Entitled: **OBJECT TYPE-DECLARATION PREFIX SYNTAX**

Enclosed are:

- ☒ 43 sheets of specification and 1 sheet(s) of drawing(s).
- ☐ An Assignment of the invention and an Assignment Recordation cover sheet.
- ☒ A verified statement to establish small entity status under 37 C.F.R. §§ 1.9 and 1.27.
- ☒ An executed declaration/power of attorney.
- ☐ An Information Disclosure Statement and form PTO-1449.
- ☒ Other: EXPRESS MAIL CERTIFICATE OF MAILING AND RETURN POSTCARD.

The filing fee has been calculated as shown below:

	(Col. 1)	(Col. 2)		SMALL	ENTITY		OTHER THAN A SMALL ENTITY	
FOR:	NO. FILED	NO. EXTRA		RATE	FEE		RATE	FEE
BASIC FEE					\$345	OR		
TOTAL CLAIMS	18 -20 =	* 0		x 9	\$0	OR	x 18	
INDEP CLAIMS	3 -3 =	* 0		x 39	\$ 0	OR	x 78	
MULTIPLE DEPENDENT CLAIM PRESENTED				x 130	\$	OR	x 260	
* If the difference in Col. 1 is less than zero, enter "0" in Col. 2				TOTAL	\$345.00	OR	TOTAL	

☒ Please charge Deposit Account No. 02-0393 in the amount of \$ **345.00** to cover the filing fee. The Commissioner is also hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 02-0393. A duplicate copy of this sheet is enclosed.

- ☒ Any additional filing fees required under 37 C.F.R. § 1.16.
- ☒ Any patent application processing fees under 37 C.F.R. § 1.17.

☐ A check to cover the filing fee is enclosed.

☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 02-0393. A duplicate copy of this sheet is enclosed.

- ☒ Any patent application processing fees under 37 C.F.R. § 1.17.
- ☐ The issue fee set in 37 C.F.R. § 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 C.F.R. § 1.311(b).
- ☒ Any filing fees under 37 C.F.R. § 1.16 for presentation of extra claims.

Respectfully Submitted,

Date: May 31, 2000

EXPRESS MAIL NO.: EK052645465US

Eunhee Park
Eunhee Park [Registration No.: 42,976]
BAKER & MCKENZIE
805 THIRD AVENUE
NEW YORK, N.Y. 10022
212-751-5700

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Bruce Hodge
Application No.: NEW APPLICATION
Filing Date: May 31, 2000
Title: OBJECT TYPE-DECLARATION PREFIX SYNTAX

Assistant Commissioner for Patents
Washington, DC 20231
BOX NEW APPLICATION

EXPRESS MAIL CERTIFICATE OF MAILING

Respectfully Submitted,

Dated: May 31, 2000

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated below and is addressed to Assistant Commissioner for Patents, Washington, D.C. 20231, BOX PATENT APPLICATION.

Date of Deposit: May 31, 2000

Express Mail mailing label number EK052645465US

Eunhee Park
Eunhee Park

Date: May 31, 2000

Eunhee Park
Eunhee Park
Registration No.: 42,976
Baker & McKenzie
805 Third Avenue
New York, New York 10022
(212) 751-5700

PTO/SB/09 (12-97)
 Approved for use through 9/30/00. OMB 0651-0031
 Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**STATEMENT CLAIMING SMALL ENTITY STATUS
 (37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)

56129050-3

Applicant, Patentee, or Identifier: Bruce Hodge

Application or Patent No.: Not Yet Assigned

Filed or Issued: Herewith

Title: OBJECT TYPE-DECLARATION PREFIX SYNTAX

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern, or organization exists.
☐ Each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

Bruce Hodge

NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

Bruce Hodge
 Signature of inventor

Signature of inventor

Signature of inventor

5/30/2000
 Date

Date

Date

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

Express Mail Label No.: EK052645465US

56129050-3

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Bruce Hodge
Application No.: NEW APPLICATION
Filing Date: May 31, 2000
Title: OBJECT TYPE-DECLARATION PREFIX SYNTAX

Assistant Commissioner for Patents
Washington, DC 20231
BOX NEW APPLICATION



EXPRESS MAIL CERTIFICATE OF MAILING

Respectfully Submitted,

Dated: May 31, 2000

Eunhee Park
Eunhee Park
Registration No.: 42,976
Baker & McKenzie
805 Third Avenue
New York, New York 10022
(212) 751-5700

CERTIFICATE OF MAILING BY EXPRESS MAIL

I hereby certify that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated below and is addressed to Assistant Commissioner for Patents, Washington, D.C. 20231, BOX PATENT APPLICATION.

Date of Deposit: May 31, 2000

Express Mail mailing label number EK052645465US

Eunhee Park
Eunhee Park

Date: May 31, 2000

[56129050-3]

Application
For
United States Letters Patent

To all whom it may concern:

Be it known that I,

Bruce Hodge

have invented certain new and useful improvements in

OBJECT TYPE-DECLARATION PREFIX SYNTAX

of which the following is a full, clear and exact
description:

Eunhee Park
Reg. No. 42,976
Baker & McKenzie
805 Third Avenue
New York, NY 10022

Express Mail Label No.: EK052645465US

OBJECT TYPE-DECLARATION PREFIX SYNTAX

5 CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims benefit of the filing date of U.S. Patent Application No. 60/136,957 entitled DYNAMIC OBJECT SYNTHESIS WITH AUTOMATIC LATE BINDING, filed
10 on June 1, 1999.

TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to computer
15 programming language and particularly, to system and method of declaring object type information in a programming language.

BACKGROUND OF THE INVENTION

20 Most of the current scripting languages on the market use Open DataBase Connectivity ("ODBC") to manipulate databases. ODBC allows a user to transfer data to and from databases using the Standard Query Language ("SQL"). Both
25 ODBC and SQL are well known standards in programming industry. However, both languages are complex and require extensive learning and practice before they can be used. An average developer of software, e.g., World Wide Web ("web") developer typically does not have the programming
30 expertise required to perform the complex functions associated with ODBC. Therefore, it is highly desirable to have a programming language that would significantly enhance the clarity and reduce the number of necessary lines of code to implement a standard query.

[NYC] 331778.1

Express Mail Label No.: EK052645465US
Date of Deposit: May 31, 2000

The presently prevalent scripting languages, PERL and Java are very powerful, but are also very complex to use and very resource-intensive to accomplish even the simplest of tasks. Therefore, it is highly desirable to have a
5 programming language syntax that is simple to implement and yet efficiently cover most of what developers need to create high-end interactive applications.

SUMMARY OF THE INVENTION

10

The present invention is directed to a programming language syntax that embeds object type declaration in the object name. The objects are self-documenting because its object type is embedded in each object. By only examining
15 the object names, therefore, methods associated with the object can be easily determined without resorting to the class definition for the object. Consequently, the language syntax in the present invention enables interpreters to process objects in an intelligent manner.
20 For example, interpreters do not have to refer back to additional information or additional files having information about the objects because the object type is embedded in each object. Not accessing additional files or memory locations can greatly improve speed and efficiency
25 of an interpreter.

With the present invention, programmers or writers of programming code need not explicitly declare variables. Consequently, the number of lines of code typically required in software code is reduced thereby reducing the
30 time to develop and implement software code. Reduced lines of code also means less memory space required to store the code. The present invention, therefore, can operate with much less memory or disk space than is required by the existing conventional programming languages. Because the

present invention need not have explicit declarations for each variable used, developing software code becomes faster and easier.

Moreover, because the type-declarations are embedded
5 with the object names, thereby rendering the objects self-contained, the code including type declaration of the present invention can be easily embedded and/or ported into a code of another language, for example, hypertext markup language ("HTML"). The present invention can also be
10 easily integrated into an interactive development environment ("IDE") such as Visual Basic and Java Symantic Cafe.

Moreover, the present invention enables programmers and/or developer to easily identify and isolate errors by
15 visual inspection, thereby enhancing greater ease in debugging codes.

In one embodiment, the object type-declaration prefix precedes the object name and explicitly declares the object type information. For example, a SQL object FirstName, may
20 be implemented as SQL@FirstName, a URL object may be implemented as URL@FirstName, environment object from an environment table may be implemented as ENV@user.

Further features and advantages of the present invention as well as the structure and operation of various
25 embodiments of the present invention are described in detail below with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements.

30 BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 shows object names having object type-declaration syntax of the present invention.

5

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to a programming language syntax that embeds object type declaration in the object name. The objects are self-documenting because its object type is embedded in each object. The present invention is related to a co-pending U.S. Patent Application Serial No. ____ (Attorney Docket No. 56129050-4) entitled DYNAMIC OBJECT SYNTHESIS WITH AUTOMATIC LATE BINDING, filed on May 31, 2000, the disclosure of which is incorporated herein in its entirety by reference thereto.

In one embodiment, the object type-declaration prefix precedes the object name and explicitly declares the object type information. Figure 1 shows object names having object type-declaration syntax of the present invention. For example, a SQL object FirstName, may be implemented as SQL@FirstName by concatenating the object type SQL with object name FirstName. A joint attribute or a separator may be an @ symbol. Similarly, a URL object may be implemented as URL@FirstName by concatenating the object type URL with object name FirstName. A joint attribute or a separator may be an @ symbol. Environment object from an environment table may be implemented as ENV@user by concatenating the object type ENV with object name user and a joint attribute @ symbol.

In the above example, the objects are self-documenting because its object type precedes the name of the object. The following syntax creates a variable object called SQLcmd that has a select command, where the account number

was sent from the previous page in a URL object called Acc and where the userId was captured from the environment table by a web server.

```
5      var@SQLcmd = "select Id from accessLog where acc
      ="+URL@Acc+" and userId = "and
      userId='"+ENV@REMOTE_USER+"'"
```

10 In the following syntax, using the connection object called myConnection, SQL statement stored in the object SQLcmd is prepared. The cursor returned from myConnection's prepare method is assigned to the cursor object named myCursor.

```
15      CURSOR@myCursor =
      CONN@myConnection.prepare(var@SQLcmd)
```

20 In the next statement, cursor object is used to fetch the Id in the table and print the information out. SQL@Id is the column name of the returned data.

```
      CURSOR@myCursor.fetch();
      Print("The user", ENV@REMOTE-USER, "Id from accessLog
      where acc =", URL@Acc, "is", SQL@Id);
25
```

30 As described, the object type-declaration prefix syntax ("OTDPS") represents the type of object embodied within the object's name. In one embodiment of the present invention, a literal string embedded with the name of the object declares the data type. Using a literal string makes the present invention far more extensible than any prior art methods.

```
      Cursor@Clients = Conn@ClientList.prepare ("select
```

```

FirstName, LastName, Phone from ClientList");
    while (Cursor@Clients.fetch())
        {print (SQL@FirstName, SQL@LastName, SQL@Phone);}

```

5 In the example above, it can be appreciated that a developer is able to recognize specific methods applied to particular objects. For example, a cursor object may be created using a connection object's prepare method. Without the Conn@ prefix before the Clientlist, however, it

10 would be difficult to know that ClientList is a Connection object. Similarly, without the cursor@ OTDPS specified in the object name, it would be difficult to know to call the Clients fetch method to retrieve the selected data from the database. Further, the SQL@ OTDPS specified in front of

15 the FirstName, LastName, and Phone objects represents that the data returned from the Clients fetch is SQL objects.

Examples of the language command set that includes the type declaration syntax of the present invention are

20 described herein below in greater detail.

1. Syntax

```
<% DynaScript %>
```

These markers delineate a DynaScript code within an HTML

25 document. This can occur more than once in a document, wherever dynamic content is needed.

```
/* multi-line comment */
```

All text between these markers are treated as a comment.

30

```
//<single line comment>
```

All text following this marker is treated as a comment up to the end of the line.

2. Literals

numbers 1, 2.3, .444444, 5.6789e+12, 0777, 0x12df
strings 'string"A"', "B string=john's name",
escape \b, \f, \n, \r, \
5 boolean true, false
null

3. Variables

Variables have this format:

10 <type>@<identifying name>

There are several basic types of variables used, and they are easily identified by their prefix (i.e., var@Cnt, URL@Name, SQL@Phone, ...).

15 The present invention includes three base classes or variables. Automatic classes are variables that are automatically created. They come into existence when first given a value, either through an assignment or function call. Created classes are variables created explicitly
20 using the CreateObject(). Default classes are objects that are created by default whenever the script is run.

var@<variable identifying name> is a general purpose automatic variable. Assigning a value to a var@object creates a variable with a scope global to the entire
25 execution. It may be destroyed when the execution ends. Examples of the var@ variables include: var@today="2000-06-01" which creates and/or sets a variable to today's date; var@year = var@today.substr(0,4) which creates and/or sets a variable to the year from a date; and var@Cnt=2 which
30 creates and/or sets variable to value 1.

4. Expression statement

Typical expression statements in the present invention may include: !var@flag, var@Cnt!=1, exists(ENV@DBQUERY),

and var@xcount=URL@URL.length().

5. Statements

In one embodiment, the present invention includes
5 singular statements as well as compound statements. An
example of a singular statement is var@Cnt=1. A compound
statement is a set of statements that may be combined into
a single statement by enclosing the statements in braces.
An example include { var@Cnt++; print(var@Cnt) }.

10

6. Control logic

6.1 If...elseif...else

This clause executes selected statements when an
expression evaluates to true. If no expression evaluates
15 to true, a default set of statements under the else is
executed. The elseif and else clauses are optional.
Multiple elseif clauses may exist. For example:

```
    if (expression) single-statement;  
    elseif (expression) single-statement;  
20    elseif (expression) single-statement;  
    elseif (expression) single-statement.
```

The compound statements may also be used in the above
example in lieu of any one of the single-statements.

25 6.2 while

The while clause in the present invention executes a
set of statements if an expression evaluates to true. The
set of statements are executed repeatedly until the
expression evaluates to false. For example:

```
30    while (expression) single-statement; or  
    while (expression) {statement; statement;}.
```

6.3 do while

The do while clause in the present invention executes

a set of statements at least once. If an expression evaluates to true, the set of statements are executed again. For example:

```
do statement while (expression); or
5 do {statement; statement;} while (expression).
```

6.4 for

The for clause in the present invention is shorthand for a typical while loop. It creates a loop that has one or more, preferably, three option expressions enclosed in parentheses and separated by semicolons. For example:

```
for (initialize; test; increment) single-statement; or
for (initialize; test; increment) {
    statement; statement; }.
```

15 6.5 labels

The labels in the present invention enables loop statements to be identified. Exit and Continue statements may target loops at higher nesting levels using labels. For example,

```
20 identifier: do / while / for clause
    loop1: while (true).
```

6.6 exit <labelname>

The exit statement followed by a label in the present invention enables a control to exit a loop such as while, do-while, and for statements, and immediately to execute the next statement following the close of the loop clause. If no label follows the exit statement, then the current loop is exited. For example,

```
30 while (var@loop1<0)
    { var@loop1++;
      if (var@loop1 == 5) exit;
    }
```

Another example may be,

```
loop1: while (var@loop1 < 5)
{ var@loop1++; var@loop2=0;
  loop2: while (var@loop2 < 5)
5    { var@loop2++; var@loop3=0;
      loop3: while (var@loop3 < 5)
        { var@loop3++;
          if (var@loop3 == 2) exit loop1;
          var@Cnt++;
10      }
    }
}
```

6.7 continue <labelname>

15 The continue statement in the present invention enables program control to exit a loop such as while, do-while, and for clauses, and immediately begin the next iteration of the same loop. Labels may be used to specify which loop when working with nested loops. When a continue
20 statement is encountered, the execution of the subsequent code within a loop is skipped and program control is returned to the beginning of the loop to begin execution of next iteration. If no label follows the continue statement, then the current loop is used as a default loop.
25 For example,

```
while (var@loop < 10)
{ var@loop1++;
  if (var@loop1 > 5) continue;
  var@Cnt++;
30 }

loop1: while (var@loop1 < 5)
{ var@loop1++; var@loop2=0;
  loop2: while (var@loop2 < 5)
```

```

    { var@loop2++; var@loop3=0;
    loop3: while (var@loop3 < 5)
        { var@loop3++;
          if (var@loop3 == 2) continue loop2;
5         var@Cnt++;
          }
        }
    }

```

10 6.8 end

The end statement in the present invention immediately terminates a program.

7 Operators

15 Table 1 includes assignment operators used in one embodiment of the present invention.

Table 1

Operators			
=	Assignment	X=0 Y=X=2	Assigns a value to a variable
++	Increment	x=2; ++x (returns 3, x==3)	Decrements operand by one and returns new value (++i) or the old value (i++)

-	Decrement	<code>x=2; --x (returns 1, x==1)</code> <code>x=2; x-- (returns 2, x==1)</code>	Decrements operand by one and returns new value (--i) or the old value (i--)
+	Addition	<code>x=2;y=3;x+y (returns 5)</code>	Adds two operands and returns sum (i+y)
	String Concatenate	<code>"str1"+"str2" (returns "strstr2")</code>	Concatenates two strings ("str1"+"str2")
-	Subtraction	<code>x=3;y=2;x-y (returns 1)</code>	Subtracts two operands and returns difference (i-y)
	Unary Negation	<code>x=3;-x (returns -3)</code>	Converts positive operands to negative (-i)
*	Multiplication	<code>5*2 (returns 10)</code>	Multiplies two operands and returns result (i*y)
/	Division	<code>15/5 (returns 3)</code>	Divides two operands and returns result (i/y)

%	Modulo	15.3 % 5 (returns 0.3)	Divides two operands and returns remainder (i%y)
&	Bitwise AND	7 & 2 (returns 2)	Bits different are set to 0
	Bitwise OR	4 1 (returns 5)	Bits different are set to 1
^	Bitwise XOR	3 ^ 2 (returns 1)	Bits different are set to 1, all other set to 0
~	Bitwise NOT	~ 5 (returns -4)	Bits are reversed from their original value (ones compliment)

&&	Logical AND	<pre>(1==1) && (2==2) (returns true) (1==1) && (2==3) (returns false)</pre>	<p>Returns a Boolean value and the operand expressions are evaluated as Boolean expressions.</p> <p>True only if both operands evaluate to True, otherwise false</p>
	Logical OR	<pre>(1==1) (2==3) (returns true) (1==2) (2==3) (returns false)</pre>	<p>Returns a Boolean value and the operand expressions are evaluated as Boolean expressions.</p> <p>True only if both operands evaluate to True, otherwise false</p>
!	Logical NOT	<pre>!(1==1) (returns false)</pre>	<p>Inverts the Boolean value of the expression evaluated</p>

==	Equality	5==5 (returns true) 5==4 (returns false)	True only if operands are the same value
!=	Inequality	5!=5 (returns false) 5!=4 (returns true)	True only if operands are NOT the same value
<	Less than	5<5 (returns false) "4" < "5" (returns true)	True if first operand is less than the second operand
<=	Less than or equal	5.1 <= 5 (returns false) 5 <=5 (returns true) "4" <= "5" (returns true)	True if first operand is less than or equal to the second operand
>	Greater than	5 > 5 (returns false) "5" > "4" (returns true)	True if first operand is greater than the second operand
>=	Greater than or equal	5.1 >= 5 (returns true) 5 >= 5 (returns false) 5" >= "4" (returns true)	True if first operand is greater than or equal to the second operand

[]	Array index	URL@Name[var@Cnt].value	Allows access to individual elements of an array. Zero is the first element.
----	-------------	-------------------------	--

7.1 Assignment shorthand

In one embodiment, the present invention also may include shorthand assignment operator notations. For example, combinations of the assignment operator and other operators may be written in shorthand notation as shown in Table 2. Table 2 lists the operators or the present invention in one embodiment.

10

Table 2

x+=y	x=x+y
x-=y	x=x-y
x*=y	x=x*y
x/=y	x=x/y
x%=y	x=x%y
x&=y	x=x&y
x^=y	x=x^y
x =y	x=x y
<<=	x=x<<y
>>=	x=x>>y

8 Functions

15 Functions include calls that do not use "variable type declaration prefix" notation, e.g., VAR@string.length().

8.1 nbsb (<mode>)

<mode> 1 = turn on, 0 = turn off

<returns> none

5 nbsb in one embodiment of the present invention
represents a none breaking space mode. If this mode turned
on, NULL characters, e.g., returned from a database query
results, may be automatically replaced by " ". This
automatic replacement method is useful when populating
10 cells in a web page table.

8.2 print (<format>, <variable list>)

<format> standard "C" printf format string

<variable list> set of optional variables

15 separated by commas, for example

<returns> formatted string

The print function in the present invention sends a
formatted string to standard output. The string may be
20 created using the same format notation used for the printf
in standard ANSI C. Examples include: print (Count
Integer: %d\n", SQL@cnt); print ("Float: %6.3f\n"
var@floatVal);

25 8.3 sprintf (<format>, <variable list>)

<format> standard C printf format string

<variable list> set of optional variable, may be
separated by commas

<returns> formatted string

30

The sprintf of the present invention returns a
formatted string, which may be created using the same
format notation used for the sprintf function in standard
ANSI C. Example include: var@Str1 = sprintf ("count

```
Integer: %d\n", SQL@cnt); var@Str2 = sprint ("Float:
%6.3f\n", var@floatVal).
```

8.4 exists (<object>)

5 <object> any object

<returns> true if the object exists, otherwise returns
false

The exists function determines whether an object has
been created. Example of a code using the exists statement
10 is: if (exists (CURSOR@CharityDeductions)) ...

8.5 errorMode (< mode >)

<mode> 1 = turn on, 0 = turn off

<returns> none

15

The errorMode function sets ODBC to report errors
verbosely and end program execution upon an occurrence of
an error. An example usage of the errorMode is:
errorMode(1).

20 8.6 alert (< text message >)

<text message> a printable text string

<returns> none

The alert function causes a message to be displayed
25 within a standard JavaScript dialog box. The dialog
remains until the user responds by clicking on the "OK"
button. An example usage of the alert function is: alert (
"An error has occurred\n" + "Please click on OK below to
continue");

30

9 Environment object

The environment object type is generated by default at
the start of a program execution. An ENV@ object may be
created for each environment variable currently defined in

the OS environment, e.g., DOS, Window, UNIX. A typical format is ENV@<name of environment variable> An example of a code using the environment object is: if (exist (ENV@REMOTE_USER)) var@str = ENV@REMOTE_USER.

5

9.1 Standard environment variables

Table 3 shows a list of standard environment variables supported in the present invention. Column 1 lists an operating system environment variable name, column 2 describes the variable, and column 3 list the variable name as used in the present invention.

10

Table 3

Operating system environment variable name	Description	Script variable name
GATEWAY_INTERFACE	The revision of the CGI that the server uses	ENV@GATEWAY_INTERFACE
SERVER_NAME	The server's hostname or IP address	ENV@SERVER_NAME
SERVER_SOFTWARE	The name and version of the server software that is answering the client request	ENV@SERVER_SOFTWARE
SERVER_PROTOCOL	The name and revision of the information protocol the request came with	ENV@SERVER_PROTOCOL

SERVER_PORT	The port number of the host on which the server is running	ENV@SERVER_PORT
REQUEST_METHOD	The method with which the information request was issued	ENV@REQUEST_METHOD
PATH_INFO	Extra path information passed to a CGI program	ENV@PATH_INFO
PATH_TRANSLATED	The translated version of the path given by the variable PATH_INFO	ENV@PATH_TRANSLATED
SCRIPT_NAME	The virtual path (e.g. /cgi-bin/program.pl) of the script being executed	ENV@SCRIPT_NAME
DOCUMENT_ROOT	The directory from which web documents are served	ENV@DOCUMENT_ROOT
QUERY_STRING	The query information passed to a program. It is appended to the URL with a "?"	ENV@QUERY_STRING

REMOTE_HOST	The remote hostname of the user making the request	ENV@REMOTE_HOST
REMOTE_ADDR	The remote IP address of the user making the request	ENV@REMOTE_ADDR
AUTH_TYPE	The authentication method used to validate a user	ENV@AUTH_TYPE
REMOTE_USER	The authentication name of the user	ENV@REMOTE_USER
REMOTE_IDENT	The user making the request. This variable is only be set if NCSA Identity Check flag is enabled, and the client machine support the RFC 931 identification scheme (ident daemon)	ENV@REMOTE_IDENT
CONTENT_TYPE	The MIME type of the query data, such as "text/html"	ENV@CONTENT_TYPE

CONTENT_LENGTH	The length of the data (in bytes or the number of characters) passed to the CGI program through standard input	ENV@CONTENT_LENGTH
HTTP_FROM	The email address of the user making the request. Most browsers do not support this variable	ENV@HTTP_FROM
HTTP_ACCEPT	A list of the MIME types that the client can accept	ENV@HTTP_ACCEPT
HTTP_USER_AGENT	The browser the client is using to issue the request	ENV@HTTP_USER_AGENT
HTTP_REFERER	The URL of the document that the client points to before accessing the CGI program	ENV@HTTP_REFERER
other environment variable may also be included		

10 URL object

Uniform resource locator ("URL") objects are created from a calling page. For example, CreateObject("URL") may

be created to synthesize URL variables. URL objects typically have string type data structure. An example usage of a URL object in the present invention is URL@<URL identifier>. An example of a code using the URL object

5 includes URL@myURL = CreateObject('URL');

10.1 Default URL object

URL@URL

URL@URL is a URL@ object representing a reserved symbol. Properties of URL@URL are described below.

10

URL@URL.length returns the number of key-value pairs in the URL@URL object. URL@URL.query returns the un-decoded URL query string. URL@URLname [<index>] returns the name of key-value pair name found at index location.

15 <index> may be an integer index value with first element = 0. The URLname method returns a string value. Examples of use include var@KeyName1=URL@URL[0].name; and var@KeyName2=URL@URL[1].name.

URL@URLvalue [<index>] returns the value of key-value pair found at index location. <index> may be an integer index value with first element = 0. The URLname method returns a string or numeric value. Examples of use include var@KeyValue1=URL@URL[0].value; and var@KeyValue2=URL@URL[1].value.

20

URL@URL.encode (<un-encode string>) method returns a URL encoded string. <un-encode string> is a string. An example of use include var@myEncodedString = URL@URL.encode(var@aString).

25

URL@URL.decode (<URL string>) method returns a decoded URL string. <URL string> is a url string which needs to be decoded. An example of the method call includes: var@decodedQuery = URL@URL.decode(URL@URL.query).

30

URL@URL.encrypt (<string to encrypt>) method returns a string which has been encrypted. <string to encrypt> is

a literal string or string variable. This method is useful in enabling secure communication of strings. Examples of use include: var@mycypherstring =

URL@URL.encrypt(var@myPlainString); and var@u =

5 "http://www.dynascript.com?Name="+URL@URL.encrypt(var@Val).

URL@URL.decrypt (<string to decrypt>) method returns a string translated back into readable characters. The string may have been originally generated by the encrypt method. <string to decrypt> is a literal string or string variable in an encrypted format. An example of use of the method include:

10 var@myPlainstring=URL@URL.decrypt(var@myCypherString).

URL@URL.validate ([<URL>]) method returns true if the supplied URL is a properly formed URL. <URL> is a URL

15 string. An example of use of the method include: if (URL@URL.validate (var@UsersURL)).

10.2 value

<parameters> none

20 <returns> string

The value function returns the value of the corresponding name. Multiple values may be passed for the same name, therefore, an index may be used to access each value. Examples of statements using the value function

25 include: var@KeyValue = URL@KeyName.value; var@KeyValue1 = URL@KeyName[0].value; var@Keyvalue2 = URL@KeyName[1].value.

10.3 length

<parameter> none

30 <returns> integer value

The length function returns the number of values associated with a key name. Examples include: var@elements = URL@KeyName.length.

11 HTML object

11.1 Default HTML object

The HTML@ object may be created by default when a program is executed. In one embodiment of the present invention, it is a reserved symbol.

The HTML@ object include header, redirect and encode functions. For example, HTML@HTML.header [<header spec>] method outputs an HTML header needed at the beginning of all HTML pages. <header spec> specifies an optional, specific type of header whose default is a standard HTML header. The method returns nothing. This method is automatically evoked if the script starts outputting without sending an HTML header. Example usage includes: HTML@HTML.header () and HTML@HTML.header('text/plain').

The HTML@HTML.redirect (<URL>) method directs the users browser to retrieve an HTML page from another URL. <URL> represents a fully declared URL. The method returns nothing. Example usage includes: HTML@HTML.redirect ('http://www.dynascript.com').

The HTML@HTML.encode (<string to encode>) method outputs a HTML encode string. <string to encode> is a literal string or string variable to be HTML encoded. The method returns nothing. Example usage includes: var@myString = HTML@HTML.encode (var@HtmlString).

12 Date object

The date object, DATE@<date identifier>, includes datetime information and methods. Example usage includes Date@lastUpdate = CreateObject('Datetime'). Its internal format may be represented as follows: yyyy-MM-dd hh:mm:ss.sss in US date style and 24 hour clock; 2000-04-15 23:59:59.012 which represents April 15th at the last second. The methods listed in Table 4 may be applied to the Date@object.

Table 4

getYear()	setYear(1999)	Four digit year (1999)
getMonth	setMonth(11)	Month(01-12)
getDate()	setDate('05/21/1999')	Date(<US style Date>)
getHours()	setHours()	Hours (24 Hour Style)
getMinutes()	setMinutes()	Minutes (00-60)
getSeconds	setSeconds	Seconds(00.000- 60.000)
getTimeZone()	setTimeZone()	TimeZone Hours Offset from GMT (0,+/-01.0 to 12.0) (defaults to system TZ)
getDay()		Day of the week (0=Sun, 6=Sat)

5 12.1 DateTime set & get method summary

The format(<pattern>) method converts a DateTime object into a formatted string. <pattern> is a date format string. The method returns character string version of date. The returned string may be assigned to any string variable. Examples include: var@Date =

DATE@myDate.format("MM/dd/yy") where "MM/dd/yy" represent date having a form, 05/10/99, for example. <pattern> also may include "yyyy-MM-dd HH:mm:ss.sss" representing 1999-05-10 13:50:43.567 format, "hh:mm" representing 01:50 PM, "dd-MON-yy" representing 10-MAY-99, and "DAY MON dd,yyyy" representing Mon MAY 10, 1999. Table 5 includes a list of

exemplary date formats in the present invention.

Table 5

Type	Pattern	Example
Year	YYYY	1999,2000,2001,...
Month	MM	01...12
	MON	'Jan'...'Dec'
Date	MM/dd/yyyy	setDate(01-12/01-31/1999-)
Day	DAY	day('Sun','Mon','Tue',...)
	day	
Hour	hh	12 hour(01-12AM/PM)
	HH	
Minute	mm	minutes (00-59)
seconds	ss	2 digit seconds (00-59)
Milliseconds	.sss	3 digit milliseconds (000-999)

5

13 String object

The string object in the present invention applies to character strings. The functions for operating on character strings are described below.

10

13.1 substr (<start position>, [<length>])

The substr method extracts a substring from a string.

<start position> may an integer. For example, 0 represents a first character, and -1 represents a first

15

character from the end of the string. <length> is a number of characters to extract. The default is the to the end of the string. Example usage includes: var@string.substr(0,4) and var@string.substr(0,var@cnt).

20

13.2 indexOf (<substring>,[<start>])

This method returns the starting location of a

substring within a string. <substring> may be a single character, string, or string variable. <start> is an integer value indicating the starting point. For example, 0 represents first character, and -1 represents last character. The method returns an integer value of starting index position of substring in string. For example, 0 represent first position, and -1 represents string not found. Example usage includes: var@index = var@string.indexOf ('test').

10

13.3 trim (<string>)

This method removes leading and trailing spaces. It is typically intended for use with SQL queries, which may have additional spaces returned in the results. <string> is a string. The method returns a string. Example usage includes var@trimmed = trim (SQL@name).

15

13.4 length

This method returns the character count of the string object. The returned value is an integer length.

20

14 ODBC database object and methods

14.1 Single connection

when only a single connection is necessary, a simple syntax using the default connection and cursor object may be used. In this case, the syntax appears more like traditional C-like function calls. Figure ? illustrates an example. Another feature of the single connection approach is that SQL statements may be inserted into the script directly and need not be enclosed within a method call, e.g., prepare9). The bindparam, execute, and fetch methods of the default cursor may be invoked without an object declaration.

30

14.2 Multiple connection

Multiple connections may be created and managed simultaneously. Each connection may also have multiple
5 result sets returned, which may be managed with cursors. Figure ? illustrates an example of code using the multiple connection.

14.3 SQL object

10 These variables include data that has been returned from a database. These objects have the format, SQL@<SQL name>.

14.4 Connection object

15 This variable represents a connection to a SQL server. Multiple database connections are allowed to be opened and queried simultaneously. The connection object has a format CONN@<connection identifier>. Examples of code using the connection object include: CONN@Greenfield = CreateObject
20 ('Connection'); CONN@Greenfield.connect(" DSN=Greenfield; UID=webuser; PWD=hodgepodge"); CURSOR@MyCur = CONN@Greenfield.prepare ("select*from clientList").

14.4.1 Default connection object

25 The default connection object CONN@CONN may be created by default whenever a script is executed. This is the connection used when the single connection scripting style is used. When connection methods are called without a specific reference to a connection object, this default
30 object is implied. Any CONN@ method may be invoked simply by calling the method as traditional function. For example, the object.method is not necessary and the call may be expressed as connect
("DSN=Greenfield;UID+webuser;PWD=hodgepodge") in place of

CONN@CONN.connect

("DSN=Greenfield;UID=webuser;PWD=hodgepodge").

14.4.2 connect (<database access string>)

5 <database access string> may include a series of
semicolon (;) separated key-value pairs which define
various connection parameters. The order of the key-value
pairs is not significant. Key-value pairs may include DSN
which is ODBC data source name, UID which is a user login,
10 and PWD which is a user password. <alternate access
string> represents string that does not explicitly declare
DSN, UID, and password. When a UID and PWD are not
required, this string may include only the data source name
in quotes, e.g., "Greenfield". The connect method returns
15 a connected property. Examples include
CONN@Greenfield.connect("DSN=Greenfield; UID=webuser;
PWD=hodgepodge"); CONN@Greenfield.connect("Greenfield");
and connect("DSN=Greenfield;UID=webuser;PWD=hodgepodge").

20 14.4.3 connected

The connected method returns true if the connection is
connected, and false if it is not. The return value is
typically a boolean true or false. Example includes: if
(!CONN@Greenfield.connected).

25

14.4.4 disconnect ()

The disconnect method disconnects a connection.
Connections are automatically disconnected upon exit. An
example of the method call includes:

30 CONN@Greenfield.disconnect ().

14.4.5 prepare (<SQL statement>)

The prepare method creates a cursor that can execute
the SQL statement. <SQL statement> may be a quoted string

which includes a single SQL statement. The method returns a Cursor object. An example of use include `CURSOR@TaxCnt = CONN@Greenfield.prepare ("select count(*) from tax_info").`

5 14.4.6 do <SQL statement>)

The do method performs a prepare and execute in one command. SQL statements that perform data inserts, updates or deletions use this command. <SQL statement> may include a quoted string which has a single SQL statement. This
10 method returns a Cursor object. An example of use includes: `CONN@Greenfield.do ("update tax_id set taxNo = 1234 where SSN = '123-45-6789'").`

14.4.7 commit()

15 The commit method records changes to the database made in previous SQL statements since the last commit() or since the opening of the connection. Following this call, changes up to this point are recorded. The changes may not be discarded using rollback() method. If a connection has
20 multiple cursors defined, changes made by all of those associated cursors are recorded. An example of use include: `CONN@Greenfield.commit().`

14.4.8 rollback()

25 The rollback method discards any changes to the database made in the previous SQL statements since the last commit() or since the opening of the connection. If a connection has multiple cursors defined, changes made by all of those associated cursors are discarded. An example
30 rollback () method call includes:
`CONN@Greenfield.rollback().`

14.4.9 setattr(<connection_attribute>,[<optional parameter>,...])

The setattr method is used to set the attributes of a connection. Parameters may be separated by commas.

<connection_attribute> may be a standard ODBC attribute.

<optional parameter> may include one or more optional

5 parameters which are specific to the

<connection_attribute>. An example of setattr method call includes:

CONN@Greenfield.setattr("SQL_attribute_autocommit_on").

10 14.4.10 Connection attributes

The connection attributes include

SQL_attribute_autocommit_on(default),

SQL_attribute_autocommit_off,

SQL_attribute_connection_timeout,

15 SQL_attribute_login_timeout, SQL_attribute_trace. These attributes are typically defined by the ODBC standard.

14.5 Cursors

The Cursor object provides access to the results

20 returned by an SQL query statement or function. Multiple cursor objects allow multiple results sets to be examined row by row simultaneously. This object has the following

format: CURSOR@<cursor identifier>. Examples of use

include: CURSOR@TaxId = CONN@Greenfield.prepare ("select

25 tax_id from taxInfor"), and CURSOR@TaxId.execute().

14.5.1 Default connection object

CURSOR@CURSOR

30 This cursor object is created by default whenever a script is executed. This cursor may be used when retrieving results using the single connection scripting style. When cursor methods are called without a specific reference to a cursor object, this default object is implied. Examples of the method call include: select

tax_Desc from tax_info where tax_id = 1234567890; execute
 (); fetch (tax_Desc). Any CURSOR@ methods may be invoked
 simply by calling the method as a graditional function; the
 object.method notation is not necessary. For example,
 5 fetch (SQL@name) may be used in place of
 CURSOR@CURSOR.fetch (SQL@name).

14.5.2 bindParam (<direction>,<script var>,<SQL param
 type>)

10 The bindParam method allows the cursor object to bind
 any variable to a parameter within the SQL statement. It
 generally is used to bind the arguments of stored procedure
 calls or select statements. The parameter is inserted in
 place of a "?" in the SQL statement. In one embodiment, a
 15 separate bindParam() call is needed for each "?" and they
 are associated in the order, i.e., first ? associated with
 the first bindParam() call. <direction> specifies the
 direction of data flow for the parameter. SQL_param_input
 is a variable used to pass data into the database.
 20 SQL_param_output is a variialbe used to pass data back from
 the database. SQL_param_input_output is a variable used to
 pass data to and from the database. <script var> includes
 a variable, e.g., URL@TaxId, var@myVar. <SQL param type>
 declares the SQL parameter type. An example of the
 25 bindParam call is: Cursor@TaxId = CONN@Greenfield.prepare
 ("select tax_id from taxInfo where name_last = ? and
 name_first = ?"); Cursor@TaxId.bindParam (SQL_param_input,
 URL@LastNm, SQL_varchar); Cursor@TaxId.bindParam
 (SQL_param_input, URL@FirstNm, SQL_varchar). Table 6
 30 includes standard SQL parameter types.

Table 6

SQL_binginter	SQL_float	SQL_real
SQL_binary	SQL_int	SQL_smallint

SQL_bit	SQL_interval	SQL_timestamp
SQL_datetime	SQL_longbinary	SQL_tinyint
SQL_decimal	SQL_longvarchar	SQL_varbinary
SQL_double	SQL_numeric	SQL_varchar

14.5.3 bindCol ([<col number>], <script var>,,)

The bindCol method binds a script variable with a column returned in a result set. Columns are specified by a number related to the order in which column values are returned. If the column number is excluded, each consecutive bindCol() is associated with the corresponding column of the result set. <column number> is an optional column number and <script var> is a script variable, e.g., URL@TaxId, to which to bind. Example of use include Cursor@My.bindCol (1, var@lastUpdDate); and Cursor @My.bindCol (2, var@acctId).

14.5.4 setPos (<number>)

The setPos method sets the row position of a cursor pointing to a result set. This method may only be used if the SQL_attribute_scrollable attribute of the cursor has been turned on. The position within the result set is an absolute from either the first or last row. A positive number moves the cursor position forward and a negative number moves it backwards. An example of use include: CURSOR@CharityDeductions.setpos(2) which moves cursor forward by 2 rows.

14.5.5 execute ()

The execute method causes any previous SQL statements to be executed by the database server. An example of use include select tax_desc from tax_info where tax_id = 123456789; CURSOR@CURSOR.execute().

14.5.6 fetch (<SQL vars>)

Each time fetch method is called, it returns values for a single row of a result set. The SQL@ variables are assigned values in the order corresponding to the result columns, i.e., SQL@arg1 = colval1, SQL@arg2 = colval2, etc.

If no variables are supplied variables are synthesized using the result set column names as the variables names. Examples of use include: CURSOR@TaxId =
CONN@Greenfield.prepare ("select tax_id from taxInfo);
10 while (CURSOR@TaxId.fetch()) { var@cnt ++; print("'%d,
%s\n", var@cnt, SQL@taxId.substr(0,10)); }.

14.5.7 free()

The free method releases the results data managed by
15 the cursor object. A call to free occurs automatically when another prepare call is made. An example of a call to the method includes: CURSOR@CharityDeductions.free().

14.5.8 setattr(<connection_attribute>,<optional
20 parameter>, ...)

The setattr method is used to set the attributes of a cursor. Parameters may be separated by a comma.
<connection_attribute> is a standard ODBC attribute, and
<optional parameter> may include one or more optional
25 parameters which are specific to the
<connection_attribute>.

14.5.9 Cursor attribute

Table 7 includes a list of cursor attributes. These
30 attributes are defined by the ODBC Standard 3.0.

Table 7

SQL_attribute_cursor_type	SQL_attribute_fetch_next
---------------------------	--------------------------

SQL_attribute_nonscrollable(default)	SQL_attribute_fetch_first
SQL_attribute_scrollable	SQL_attribute_fetch_last
SQL_attribute_forward_only (default)	SQL_attribute_fetch_prior
SQL_attribute_cursor_static	SQL_attribute_fetch_absolute
SQL_attribute_cursor_dynamic	SQL_attribute_fetch_relative

15 DB query language

The present invention is enabled to support a subset of the standard SQL query language. These statements are those that are likely to need to access a database from within a script of the present invention.

15.1 Standard SQL syntax allowed

Table 8 includes the SQL syntax supported in the present invention.

Table 8

Create a table	create table employee_list (id_number int(10) not null, lastname varchar(40) not null, firstname varchar(40) not null, phonenumber char(12) null)
Delete a table	drop table employee_list

Insert rows	insert into employee_list (id_number, lastname, firstname) values (121212, "Abelson:", "Alice") insert into employee_list (id_number, lastname, firstname) values (232323, "Benson:", "Bart") insert into employee_list (id_number, lastname, firstname) values (343434, "Clarkson:", "Clyde")
Delete rows	delete from employee_list where id_number = 343434
Update rows	update employee_list set phonenumber = "123-456-7890" where lastnmae = "Ableson", and firstname = "Alice"
Select from database	select * from employee_list order by lastname, firstname
Execute a stored procedure	exec GetAreaCode, 123 or BEGIN GetAreaCode (123) END;

16 Debugging

5 In the present invention, setting the debug mode at the start of a script allows the developer to output information that is not normally available. Debugging output is written to a separate file, e.g., debug.txt, in the same directory as the scripts executable so that it does not affect the normal output of the script.

10

DEBUG@DEBUG

DEBUG@DEBUG object is created by default at the start

of a script in the present invention. The mode method is used to enable and disable the scripts debugging features.

The debug method has the following syntax:

- 5 DEBUG@DEBUG.mode (<hexadecimal bit map>) where <hexadecimal bit map> is hexadecimal value (0xhhhhhhhh) where h is a hexadecimal digit (0-9, a-f). The hexadecimal values shown in Table 9 below may be combined or added into a single value.

10 Table 9

DEBUG_IO	0x00000001	Enable input and output of debugging information to debug.txt
not used	0x00000002	
not used	0x00000004	
not used	0x00000008	
DEBUG_ODBC	0x00000010	Set to dump ODBC commands
DEBUG_FETCH	0x00000020	Set to dump fetch variables
DEBUG_CALL	0x00000040	Set to dump procedure call variables
DEBUG_ASSIGNMENT	0x00000080	Set to dump all variable assignments
not used	0x00000100	
not used	0x00000200	
not used	0x00000400	
not used	0x00000800	
not used	0x00001000	
not used	0x00002000	
not used	0x00004000	
not used	0x00008000	
DEBUG_OUTPUT	0x00010000	Set to output debug data to client

DEBUG_FILE-APPEND	0x00020000	Set to output debug data to file in append mode
DEBUG_FILE_NEW	0x00040000	Set to output data to file in overwrite mode
DEBUG_PERSIST	0x00080000	Set to carry debug on to all other pages
not used	0x00100000	
not used	0x00200000	
not used	0x00400000	
not used	0x00800000	
not used	0x01000000	
not used	0x02000000	
not used	0x04000000	
not used	0x08000000	
not used	0x10000000	
DEBUG_AND_MASK	0x20000000	Set to AND out all lower non-set bits
DEBUG_OR_MASK	0x40000000	Set to OR in all lower bits
not used	0x80000000	

While the invention has been particularly shown and described with respect to a preferred embodiment thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and details may be made therein without departing from the spirit and scope of the invention.

CLAIMS

Having thus described our invention, what we claim as new,
and desire to secure by Letters Patent is:

5

1. An object type-declaration syntax comprising:
an object identifier;
an object type indicator indicating a type of an
object identified by the object identifier; and
10 a join attribute associating the object identifier
with the object type indicator.

2. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator is embedded as
15 part of the object identifier.

3. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator includes
database object type.

20

4. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator includes SQL
("SQL") database object type.

25 5. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator includes
connection ("CONN") database object type.

30 6. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator includes cursor
("CURSOR") database object type.

7. The object type-declaration syntax as claimed in
claim 1, wherein the object type indicator includes

universal resource locator ("URL") object type.

8. The object type-declaration syntax as claimed in claim 1, wherein the object type indicator includes
5 environment ("ENV") object type.

9. The object type-declaration syntax as claimed in claim 1, wherein the object type indicator includes
10 hypertext markup language ("HTML") object type.

10. The object type-declaration syntax as claimed in claim 1, wherein the object type indicator includes
extensible markup language ("XML") object type.

11. The object type-declaration syntax as claimed in claim 1, wherein the joint attribute is concatenated to the
15 object type indicator.

12. The object type-declaration syntax as claimed in claim 11, wherein the object identifier is concatenated to
20 the joint attribute.

13. The object type-declaration syntax as claimed in claim 1, wherein the joint attribute is concatenated to the
25 object identifier.

14. The object type-declaration syntax as claimed in claim 13, wherein the object type indicator is concatenated
30 to the joint attribute.

15. The object type-declaration syntax as claimed in claim 1, wherein the object identifier includes dynamically
evaluated expressions.

16. A method of declaring an object type in a programming language, comprising:
embedding an object type indicator with an object identifier name.

5

17. A method of declaring an object type in a programming language, comprising:
prepending an object type indicator with an object identifier name.

10

18. The method of declaring an object type in a programming language as claimed in claim 16, wherein the step of embedding includes:

15 joining the object type indicator with the object identifier name with a joint symbol.



OBJECT TYPE-DECLARATION PREFIX SYNTAX

ABSTRACT OF THE INVENTION

A programming language syntax that embeds object type
5 declaration in the object name. The objects are self-
documenting because its object type is embedded in each
object. In one embodiment, the object type-declaration
prefix precedes the object name and explicitly declares the
object type information. For example, a SQL object
10 FirstName, may be implemented as SQL@FirstName, a URL
object may be implemented as URL@FirstName, environment
object from an environment table may be implemented as
ENV@user.

1/1

Figure 1



56129050-3

DECLARATION AND POWER OF ATTORNEY

As the below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled **OBJECT TYPE-DECLARATION PREFIX SYNTAX**, the specification of which is filed herewith.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

- None -

Express Mail Label No.: EK052645465US

[NYC] 331861.1

Page 1 of 3

I hereby claim the benefit under Title 35, United States Code, §§ 119(e) of any United States provisional application(s) listed below:

PRIOR PROVISIONAL APPLICATION(S)

Application Number

Filing Date

60/136,957

June 1, 1999

I hereby claim the benefit under Title 35, United States Code § 120, of any United States application(s) listed below or under § 365(c) of any PCT international application(s) designating the United States of America listed below, and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

PARENT APPLICATION(S)

- None -

And I hereby appoint James David Jacobs (Reg. No. 24,299), Victor DeVito (Reg. No. 36,325), Harry K. Ahn (Reg. No. 40,243), Frank Gasparo (Reg. No. 44,700) and Eunhee Park (Reg. No. 42,976) my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Please address all communications regarding this application to:

BAKER & MCKENZIE
805 Third Avenue
New York, New York 10022

Please direct all telephone calls to Eunhee Park at (212) 751-5700.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful and false statements may jeopardize the validity of the application or any patent issued thereon.

First Inventor: Bruce Hodge

Inventor's Signature:

Date: 5/30/2000

Residence: 54 Wilton Road
Greenfield, New York 12833

Citizenship: USA

Post Office Address: Same as above.

MAY 30 2000 17:10

5188932591

PAGE.03